

RECEIVED
CENTRAL FAX CENTER
OCT 29 2007

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A communication apparatus comprising:

an antenna for transmitting and/or receiving a wireless signal,

a signal processing circuit for processing a signal corresponding to a wireless signal received by the antenna,

a conductive case for surrounding and housing all or part of the signal processing circuit, and

an electro-magnetic wave absorber with one surface adjacent a predetermined area of the conductive case for absorbing electro-magnetic waves and thereby reducing electro-magnetic waves reaching a user of the communication apparatus, and

a conductive member provided at another surface of the electromagnetic wave absorber and being electrically connected to the conductive case.

2. (Currently Amended) A communication apparatus as set forth in claim 1, wherein said electro-magnetic wave absorber and said conductive layer member are arranged between said conductive case and a head of a user of the communication apparatus.

3. (Previously Presented) A portable telephone comprising:

an antenna for transmitting and/or receiving a wireless signal;

a microphone for generating a sound signal corresponding to an input sound;

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

a circuit for generating a wireless signal corresponding to said sound signal generated by said microphone;

a conductive shield case surrounding and housing all or part of said circuit;

an electro-magnetic wave absorber with one surface in contact with a predetermined area of the shield case for absorbing electro-magnetic waves and thereby reducing the amount of electro-magnetic waves reaching a user of said telephone device; and

a conductive member provided at another surface of the electric wave absorber and being electrically connected to the conductive shield case.

4. (Currently Amended) A portable telephone as set forth in claim 3, wherein said circuit comprises:

a transmitting circuit for generating a wireless signal corresponding to a sound signal from the microphone,

a receiving circuit for generating a sound signal in response to a wireless signal received by the antenna and outputting the sound signal, and

a printed circuit board containing the transmitting circuit and the receiving circuit, and wherein

the shield case surrounds and houses ~~all or part of~~ the transmitting and receiving ~~circuit circuits and the printed circuit board~~ to prevent electromagnetic interference between the transmitting and receiving ~~circuit circuits~~ and the antenna.

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

5. (Previously Presented) A portable telephone as set forth in claim 3, wherein said electro-magnetic wave absorber is arranged at an area at a surface of said shield case close to a head of a user of the portable telephone at the time of a call.

6. (Previously Presented) A portable telephone as set forth in claim 3, wherein said electro-magnetic wave absorber is closely bonded to an area at a surface of said shield case close to a head of a user of the portable telephone at the time of a call.

Claim 7. (Canceled).

8. (Currently Amended) A portable telephone as set forth in claim 3, wherein said conductive ~~layer~~ member and said shield case are connected by a metal wiring.

9. (Currently Amended) A portable telephone as set forth in claim 3, wherein the conductive ~~layer~~ member comprises a metal plate fixed to the shield case and
the electro-magnetic wave absorber is formed by inserting a member between the surface of the shield case and the metal plate.

10. (Previously Presented) A portable telephone as set forth in claim 3, wherein said electro-magnetic wave absorber includes a magnetic loss material.

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

11. (Previously Presented) A portable telephone as set forth in claim 10, wherein said electromagnetic wave absorber is made in a desired shape from a mixture of said magnetic loss material and a synthetic resin.

12. (Currently Amended) A portable telephone as set forth in claim 4, further comprising

a switching circuit and a feeder on the printed circuit board for supplying the wireless signal from the transmitting circuit to the antenna and supplying the wireless signal from the antenna to the receiving circuit and

said feeder used for connecting the switching circuit and the antenna, and the electro-magnetic wave absorber is closely bonded to a portion of the shield case located between the feeder and the ~~receiver~~ receiving circuit.

13. (Previously Presented) A portable telephone as set forth in claim 3, wherein said shield case is made of an insulating material and has a conductive layer formed on its surface and

said conductive layer is connected to a layer of a ground level voltage of said printed circuit board.

14. (Previously Presented) A portable telephone as set forth in claim 4, wherein said shield case is made of a conductive material and is connected to a layer of a ground level voltage of said printed circuit board.

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

15. (Previously Presented) A portable telephone as set forth in claim 4, further comprising an outer housing made of an insulating material for housing said transmitting and receiving circuit, said shield case, said electro-magnetic wave absorber, and said microphone, wherein

said receiving circuit is arranged in the vicinity of one end of said housing,
said microphone is arranged in the vicinity of another end of said housing, and
said antenna is a retractable antenna able to extend from said one end in the longitudinal direction of said housing.

16. (Previously Presented) A portable telephone as set forth in claim 15, further comprising

a switching circuit on said printed circuit board for supplying said wireless signal from said transmitting circuit to said antenna, and for supplying said wireless signal from said antenna to said receiving circuit and

a feeder for connecting said switching circuit and said antenna, wherein
said electro-magnetic wave absorber is closely bonded at the portion of said shield case located between said receiving circuit and said feeder.

Claims 17. – 18. (Canceled)

19. (Currently Amended) The communication apparatus of claim 1, wherein the

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

~~electro-magnetic wave absorber is not~~ conductive member is electrically connected to a ground layer of the signal processing circuit.

20. (Currently Amended) The portable telephone of claim 3, wherein the ~~electro-magnetic wave absorber is not~~ conductive member is electrically connected to a ground layer of the circuit.

Please add the following new claims:

21. (New) The communication apparatus of claim 1, further comprising an outer housing separate from said shield case, which surrounds and confines said conductive case, said electro-magnetic wave absorber, said signal processing circuit, and said conductive member; and

wherein said electro-magnetic wave absorber is arranged between said conductive case and said outer housing on a side of the conductive case facing a head of a user of the communication apparatus when in use.

22. (New) The communication apparatus of claim 21, wherein said antenna is provided substantially outside of said outer housing, and a feeder is formed within the outer housing for connecting said antenna and said signal processing circuit.

23. (New) The communication apparatus of claim 21, wherein said conductive case surrounds substantially the entire signal processing circuit.

Appl. No. 09/876,411
Amdt. Dated October 24, 2007
Reply to Office Action of March 12, 2007

24. (New) The portable telephone of claim 3, further comprising an outer housing separate from said shield case, which surrounds and confines said conductive shield case, said electro-magnetic wave absorber, said microphone, said circuit, and said conductive member; and

wherein said electro-magnetic wave absorber is arranged between said conductive shield case and said outer housing on a side of the conductive shield case facing a head of a user of the portable telephone when in use.

25. (New) The portable telephone of claim 24, wherein said antenna is provided substantially outside of said outer housing, and a feeder is formed within the outer housing for connecting said antenna and said circuit.

26. (New) The portable telephone of claim 3, wherein said conductive case surrounds substantially the entire signal processing circuit.

27. (New) The communication apparatus of claim 1, wherein said electro-magnetic wave absorber includes a magnetic loss material.